

## Specifications

Test mode: Kinetic, End point, Two point

Wavelength: 7 standard filters: 340, 405, 450, 510, 546, 578, 630nm, 1 free position

Light Source: Long-life tungsten-halogen lamp 6V/10W, auto-sleep function

Display: 7.0" TFT LCD with touch screen, 800x480 pixels.

Printer: Built-in thermal printer, 57mm printer paper

Temperature Control: By means of Peltier elements, Room temperature: 25°C, 30 °C and 37°C

Flow cell&Cuvettes: Measuring volume: 32 µL, Optical path: 10mm

Absorbance variation: Outside 0.0001 Abs, inside ≤0.005Abs

Photometric Range: 0-3 Abs

Memory: DDR2 RAM 512MB, Flash: 256 MB, Over 300 programs, 200000 results can be stored

Interface: 1 USB port for keyboard , mouse , printer

1 USB port for PC connection, data transmission

Operating Environment: Temperature: 10°C~30°C, Humidity: 30%~80%

Power Requirement: Wide power supply: AC 100-240V, 50/60Hz

Product Dimension: L355\*W288\*H164mm

Package Dimension: L430\*W355\*H260mm

Weight: 5kg

Liver Function: ALT AST ALP T-BIL D-BIL TP ALB TTT CHE  $\text{NH}_3$

Renal Function: BUN CRE UA URE CO2-CP Y-GT

Lipids: T-CHO TG HDL-C LDL-C

Cardiac Function: CK CK-MB LDH

Immun Proteins: IGA IGG IGM C3

Others: GLU HGB AMS...

**Excl. Mktd. by**

**FINOVA HEALTHCARE PVT. LTD.**

**10, 3rd Floor, Savitri Chamber, D Block Central Market,**

**Opp. PVR Cinema, Prashant Vihar, Delhi-110085**

**Email : [finovahealthcare@gmail.com](mailto:finovahealthcare@gmail.com), [sales@psrbiochem.in](mailto:sales@psrbiochem.in)**



### Features

**Stable quality, Latest model with flexible software system , Less and easy maintenance**

- Latest Linux software system
- 7.0" inch LCD Color touch screen, 800x480 pixels
- Multifunctional incubator
- Flow cell and cuvette testing modes
- Universal power supply
- Light source hibernate function making lamp long life time
- The storage capacity of data is large, and can store 200000 sample results

*Easy to change the lamp, no need open the cover*

